



it's time to get wise

about **flooring installation** with our other **market-leading** products:

When it comes to flooring installation, **Floorwise** is the name for **quality** and **value**!

For **over 35 years** Floorwise has been the **number one choice** for flooring professionals.

Reliable service, through an exclusive network of distributors, and the consistent quality of our products has earned Floorwise an enviable reputation.

Floorwise strives to deliver excellence in innovation too, with a continuous development programme aimed at meeting the evolving needs of both consumers and installers alike.

for **sales** and **enquiries** contact:



find us on @floorwisehq or visit us at www.floorwise.co.uk

adhesives + screeds



Uniclass L53611	EPIC E485
CI/SfB (43)	T
<small>October 2021</small>	



adhesives + screeds

© Floorwise Group Ltd, 2021



wiseup@
www.floorwise.co.uk

wiseup@
www.floorwise.co.uk

Floorwise supply the flooring professional with a quality and versatile range of adhesives & levelling compounds which won't let you down on the job!

The perfect floor needs a perfect base and our range of products cover every need in order to achieve this! Then what you must have is an adhesive that holds fast and lasts the course. Floorwise won't let you down, and absolutely **won't come unstuck** when it comes to product quality, availability or supply!



- pages **3-4** **levelling & smoothing** compounds
- page **5** **levelling & smoothing** compound **suitability chart**
- pages **6-7** **flooring** adhesives
- pages **8-9** **cartridge** adhesives & sealants
- pages **10-11** **spray** adhesives
- page **12-13** **canister spray** adhesives
- page **14** adhesive **suitability chart**
- page **15** **floorwise distribution** network

wise up to floorwise
quality & value guaranteed

F5GOLD Pro-Screed Gold 2 Part rapid setting latex polymer levelling & smoothing compound

F5GOLDLL Pro Screed Latex Liquid

A versatile 2 part latex polymer levelling and smoothing compound with excellent flow and adhesion properties. The unique formulation qualities allow the compound to be installed without the need to prime on most sub floors. The ultra fast setting compound can be walked on after as little as 90 minutes and floorcoverings can be installed after just 4 hours. It can be applied from depths of 2mm to 12mm in one application and up to 30mm with aggregate. It is moisture tolerant and can be laid under and over DPM's and can be applied over most underfloor heating systems.

- **Rapid Setting**
Walk on after 90 minutes
Install floorcoverings after 4 hours
- **Excellent flow**
and application properties
- **Suitable for use**
over old adhesive residues
- **Moisture tolerant**
can be used below and over DPM's
- **No priming necessary**
on most subfloors
- **Perfect for timber substrates**
- **Suitable for use**
with Underfloor heating systems
- **Low odour**
- **Protein, ammonia & casein free**

Walk on time:	90 minutes
Working time:	Approximately 20 minutes
Apply Floorcovering:	Typically 4 hours (3 hours for ceramic tiles)
Compressive Strength:	C16 after 28 days
Application Thickness:	Featheredge to 10mm unfilled From 10mm to 30mm filled (3mm granite chippings)
Coverage:	5-6m² @ 3mm per 20kg bag + 5L liquid



5L



20kg



levelling & smoothing compounds

levelling & smoothing compound suitability guide

F5FEA Pro Screed Feather Edge ultra fine, rapid setting levelling & patch repair compound

An ultra-fine rapid setting, fast drying, high polymer leveling and patch repair compound. The unique formulation truly delivers a feather edge from 0-3mm, perfect for feathering and patching depressions, trowel marks, ridges, gouges and joints in subfloors, as well as smoothing over screw heads and joints between sheets of plywood. With outstanding adhesion properties the compound can be used without a primer and can be applied over most underfloor heating systems.

- **Rapid drying**
- **Install floorcoverings** after 15 minutes
- **Excellent adhesion properties**
- **Perfect for timber substrates**
- **No priming necessary**
- **Suitable for use** with underfloor heating systems
- **Protein free**

Walk on time: **15 minutes**
 Working Time: **Approximately 10-15 minutes**
 Apply Floorcovering: **After 15 minutes**
 Application thickness: **0 to 3mm**
 Coverage: **45m² @ 1mm per 10kg bag mixed with 5L water**



Product	F5GOLD	F5FEA
Size	20Kg & 5L	10Kg
Coverage	5-6m² @ 3mm per 20kg bag+ 5 L liquid	45m² @ 1mm per 10kg bag+ 5 L water
Working time at 20°C	15-20 minutes	15 minutes
Time to foot traffic at 20°C	90 minutes	15 minutes
Time to lay floorcovering	absorbent non absorbent	15 minutes
Application thickness	min (mm) unfilled max (mm) unfilled max (mm) filled	0mm 3mm N/A
Compressive strength 28 day	C16	C12
Flexural strength 28 day	F7	F5
EN 13813 class / EN 1504-3 class	CT-C16-F7	CT-C12-F5

Application method	F5GOLD	F5FEA
Trowel	✓	✓
Pump application		
Aeration roller recommended	✓	

Product characteristics	F5GOLD	F5FEA
Rapid setting	✓ Walk on - 90 minutes install floorcovering 4 hours	✓ Walk on - 15 minutes install floorcovering 15 minutes
Excellent flow	✓	
Suitable for use over old adhesive residues	✓	
No priming necessary	✓	✓
Suitable for rigid timber substrates	✓	✓
Suitable for use with underfloor heating	✓	✓
Suitable for biologically sensitive areas	✓	✓
Suitable for high temperature areas	✓	✓
Moisture tolerant – can be used below and above DPM's	✓	
Low odour	✓	✓
Protein, ammonia & casein free	✓	✓

Sub floor suitability	F5GOLD	F5FEA
Concrete, sand/cement screeds and other solid absorbent surfaces	✓	✓
Power floated concrete	✓	✓
Ceramics, porcelain, terrazzo, marble, granolithic and other non absorbent surfaces	✓	✓
Anhydrite screeds*	✓*	✓*
Old adhesive residues (moisture tolerant)	✓	
Surface DPM, epoxy & polyurethane coatings	✓	
Flooring grade plywood	✓	✓
Rigid timber floors	✓	✓
Rigid vinyl tiles	✓	✓
Rigid steel/metal (non flexing & corrosion free)	✓	
Flooring grade asphalt/bitumen	✓	✓
Fibre cement sheet & tile back boards	✓	✓
Fibreglass	✓*	

* when primed

F555 All-purpose Flooring Adhesive

This all-purpose flooring adhesive is an acrylic based, non-staining adhesive formulated to give excellent initial grab and a high quality, durable bond when dry.

Suitable for permanently bonding carpets & vinyl floorcoverings onto a wide variety of subfloors. It is low in VOC's and the adhesive is suitable for application over most underfloor heating systems.

Coverage: approx. 45–55m² per 15kg bucket

- Excellent initial grab
- High performance bond
- Great coverage
- Easy application
- Suitable for use with underfloor heating systems
- Low VOC



15kg

F542 MS Polymer Wood Flooring Adhesive

The MS polymer wood flooring adhesive is a high performance, flexible, single component, solvent and water-free adhesive for permanent bonding of all types of wood flooring. Compatible with most underfloor heating systems, the advanced polymer adhesive is both safe and clean to use.

Coverage: approx. 16-24m² per 16kg bucket.
approx. 10 linear metres of 8mm bead per 600ml sausage.

- Permanent elastic bond
- One component
- Rapid curing
- Excellent initial grab
- High performance bond
- Easy application
- Solvent free
- Low VOC
- Suitable for use with underfloor heating systems



16kg



600ml

F523 Carpet Tile Tackifier

Carpet Tile Tackifier is a solvent free, non staining, acrylic polymer dispersion adhesive formulated to produce a permanent tacky finish when dry.

Suitable for bonding carpet tiles with PVC, polypropylene and bitumen with fibre backings to a wide variety of subfloors; It is low in VOC's and the adhesive is suitable for application over most underfloor heating systems.

Coverage: approx. 140–160m² per 15kg bucket
approx. 230–250m² per 25kg container

- Easily applied
- Fast drying
- High permanent tack (pressure sensitive)
- Tiles can be lifted and replaced



25kg



15kg

F538 Water Resistant Wood Adhesive

This non-plasticised, cross linking PVA emulsion adhesive is specially formulated for wood bonding in all cases where a fast set, high bond strength and excellent water resistance are required. Suitable for virtually all woods, wood decoratives and high pressure laminates. Conforms to BSEN 204:1991:D3 and BS4071 for creep resistance.

Coverage: approx. 60–80 linear metres of 3mm bead per 500ml bottle

- Fast drying
- High initial grab
- High shear strength
- Great temperature resistance



made in the UK



500ml

F500 Silicone Joint Sealant

This silicone joint sealant is specially formulated for use in providing a waterproof, hygienic, flexible seal, which is resistant to mildew and mould growth.

Coverage: approx. 11 linear metres of a 6mm bead per cartridge

- Interior and exterior applications
- High movement accommodation
- Excellent adhesion
- Lasts up to 25 years
- Contains fungicide

310 ml



F579 Fast Set Floor-Fix PU Adhesive

Is a fast setting polyurethane adhesive for both interior and exterior applications. It has super quick grab and excellent grab bond strength suitable for a wide range of materials and surfaces.

Coverage: approx. 40 linear metres of a 3mm bead per cartridge

- Super quick grab adhesive
- Interior/exterior applications
- Excellent bond strength
- Bonds to most substrates

310 ml



F577 Floor Fix Mastic Adhesive

Is a high strength, gap filling cartridge adhesive for bonding a wide variety of materials to most surfaces.

Coverage: approx. 11 linear metres of a 6mm bead per cartridge

- High initial grab
- Excellent gap filling
- Excellent bond strength
- Bonds to most substrates

310 ml



FLE290 Flexy Fix MS Polymer Adhesive

An extremely versatile, high performance flexible, rapid curing MS polymer adhesive for bonding a wide variety of materials to most surfaces. Approved for direct stick stair nosings applications and compatible with most underfloor heating systems, this advanced polymer adhesive is easy and clean to apply.

Coverage: approx. 15 linear metres of a 5mm bead per cartridge

- Permanent elastic bond
- Rapid curing
- Excellent initial grab
- High performance bond
- Easy application
- Solvent free
- Low VOC
- Approved for direct stick stair nosing applications
- Suitable for use with underfloor heating systems

290 ml



F580 Contact Adhesive

A versatile synthetic rubber/resin contact adhesive for bonding a wide variety of floorcoverings, PVC coving and skirtings to a wide variety of floor & wall surfaces.

Coverage: approx. 27.5m² on a single non-porous surface per 5 Litre can

- Fast drying
- High initial grab
- High shear strength
- Great temperature resistance



F599 Heavy Duty Spray Adhesive

This market-leading spray adhesive can be used to fix a wide variety of floorcoverings onto most sub floors.

Coverage: approx. 3m² per can onto a single non-porous surface

- Higher solids – more adhesive per can
- Higher coat weight – more adhesive to the surface
- Excellent bond strength
- Super quick drying

**Not suitable for highly plasticised Vinyls or PVC*

500ml



F592 Contact Spray Adhesive

A versatile synthetic rubber/resin contact adhesive for permanently bonding a wide variety of materials to most surfaces. It has high temperature resistance making it suitable for most underfloor heating systems.

Coverage: approx. 3m² per can onto a single non-porous surface

- High adhesive content
- Excellent bond strength
- High temperature resistance (up to 90°C)
- Quick drying
- Easy to use
- CFC free

**Not suitable for highly plasticised Vinyls or PVC*

500ml



F590 Solvent Cleaner

A powerful solvent based cleaner to quickly remove adhesive, oils, grease and other organic substances. Perfect for cleaning larger canister guns and hoses.

- Powerful action
- Quick and easy to use

500ml



F595 Vinyl Spray Adhesive

Is a plasticiser-resistant adhesive for permanently bonding a variety of floorcoverings, including vinyl and PVC to a wide range of subfloors.

Coverage: approx. 3m² per can onto a single non-porous surface

- Plasticiser resistant
- Excellent bond strength
- Easy to use

500ml



F598 Spray Adhesive

A good all round spray adhesive for permanently bonding a wide variety of floorcoverings onto most subfloors.

Coverage: approx. 3m² per can onto a single non-porous surface

- Strong bond
- Quick drying
- Easy to use

**Not suitable for highly plasticised Vinyls or PVC*

500ml



made in the UK

F592C Contact Spray Adhesive

A versatile synthetic rubber/resin contact adhesive for permanently bonding a wide variety of materials to most surfaces. It has high temperature resistance making it suitable for most underfloor heating systems.

Coverage: approx. 100-150m² on a single sided application per 19.5L canister, dependent upon the porosity of the subfloor.

- Superfast spray action
- Long open time
- Great grab
- Strong bond strength
- Great temperature resistance



**Not suitable for highly plasticised Vinyls or PVC*

19.5L

F593C Super Contact Spray Adhesive

A versatile synthetic one part rubber/resin contact adhesive for permanently bonding a wide variety of materials to most surfaces. It is formulated with a high adhesive content which improves the initial grab and final bonding strength. With a high temperature resistance it is suitable for most underfloor heating systems.

Coverage: approx. 100-150m² on a single sided application per 19.5L canister, dependent upon the porosity of the subfloor.

- High adhesive content
- Superfast spray action
- Long open time
- Excellent grab
- Strong bond strength
- Great temperature resistance

19.5L

**Not suitable for highly plasticised Vinyls or PVC*

F594C Carpet Tile Tackifier Spray Adhesive

This high solids spray adhesive remains permanently tacky when dried, perfect for holding down carpet tiles, underlays and other floorcoverings which may require uplifting at a later date. Suitable to bonding to a wide variety of subfloors.

Coverage: approx. 300-500m² on a single sided application per 19.5L canister, dependent upon the weight of application and porosity of the subfloor.

- Superfast spray action
- High adhesive content
- Fast drying
- Exceptional coverage
- Low odour

19.5L

** Not suitable for PVC backed carpet tiles*

F7252 Standard Gun for spray canisters

Durable and lightweight gun with versatile interchangeable **9501** spray tip.

F7254 Hose for spray canisters

Lightweight yet durable nylon core with synthetic rubber coating. Compete with easy fit connectors.

12ft & 18ft

F7251 Premium Gun for spray canisters

Strong Aluminium Alloy Body with versatile interchangeable **9501** spray tip.

F7253 Standard Gun & Wand for spray canisters

Durable and lightweight gun with 47cm extension wand, complete with versatile interchangeable **9501** spray tip.

